

LOADING RAMPS AUSBAU

PRO SERIES



6-12

TONS

The most popular series of mobile ramps among customers, always available in stock. The length of the inclined part is 8000–8500 mm, the horizontal platform is 2500–2700 mm. The width of the carriageway is 2000 mm, which makes it convenient to load the left and right rows of pallets into the truck trailer.

SRT SERIES



6-12

TONS

Most often used in cramped conditions, in small areas. The length of the inclined part is 8000–8500 mm. The width of the carriageway is 2000 mm (it is convenient to load the left and right row of pallets). The short horizontal platform is 1000 mm. Therefore, the series is suitable for loading when the truck body floor can be used as a horizontal platform.

LNG SERIES



6-12

TONS

The main advantage of this series is the dimensions of the ramp, comfort and convenience. The extended horizontal platform of 2800–3100 mm provides more space for leveling the forklift before entering the truck. The length of the inclined part of 9200–9900 mm differs from other series of ramps, making it easier to lift / lower the forklift. The width of the carriageway is 2000 mm, which is ideal for loading/unloading standard loads.

SPCL SERIES



6-50

TONS

This series of ramps solve non-standard customer needs and is made to order. Carriageway widths from 2000 to 6000 mm, load capacities from 6 to 50 tons, additional options, the possibility of a collapsible ramp, and other characteristics that can be changed to suit the customer's order.

ST SERIES



6-12

TONS

A series of standard stationary ramps without a horizontal platform. The length of the inclined part is 8000–12000 mm, and the width of the roadway is 2000 mm. If there is no need for ramp mobility, this series is the best solution, especially for organizing access to a highly located warehouse from the ground.

STB SERIES



6-12

TONS

A series of stationary ramps with a horizontal platform. The length of the inclined part is 8000–10000 mm, and the width of the roadway is 2000 mm. The main difference from the ST series is the presence of a horizontal platform 2500 mm long, which in turn makes it possible to stop and level the forklift before entering the warehouse / truck body. A small bridge on the hinges allows you to level minor differences in height between the ramp and the truck body.



+48 22 390 64 43
+49 302 555 98 68
+40 37 170 02 36

+36 1 800 16 67
+37 05 214 10 33
+42 023 409 21 33

+421 23 333 10 75
+31 970 102 808 98
+38 044 599 30 15



mail@av-exim.com